

Tyrone Camarero Specifications

Tyrone

Camarero: SSI100C3R-48

Key Feature

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
- Up to 2TB Intel® Optane™ Persistent Memory, in 8 DIMM slots"
- 2 PCIe 4.0 x8, 1 PCIe 4.0 x16 , 1 PCIe 4.0 x8 (in x16 slot) ,3 PCIe 3.0 x8
- M.2 Interface: 1 SATA/PCIe 3.0 x4, M.2 Form Factor: 2280/22110
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with Intel® i210 Gigabit Ethernet Controller
- 8x 3.5"/2.5" hot-swap SAS drive bay with SES3
- 2x 80mm PWM Rear Chassis Fans (9.4k RPM), 3x 80mm high-performance fan(s) (9.4k RPM)
- 1200W (1 + 1) Redundant Titanium Level Certified High-Efficiency Power Supply



Processor/Cache		Drive bays	
Processor	3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP	Drive bays	8x 3.5"/2.5" hot-swap SAS drive bay with SES3
Chipset	Intel® C621A	Peripheral Drives	3x standard 5.25" drive bay
System Memory	8 DIMM slots, Up to 2TB Intel® Optane™ Persistent Memory 200 Series, Up to 2TB 3DS ECC LRDIMM, DDR4-3200MT/s; Up to 2TB 3DS ECC RDIMM, DDR4-3200MT/s	Power Supply	Power Supply 1200W (1 + 1) Redundant Titanium Level Certified High-Efficiency Power Supply
Expansion Slot	PCI-Express 1 PCIe 4.0 x16, 1 PCIe 4.0 x8 (in x16 slot), 2 PCIe 4.0 x8, 3 PCIe 3.0 x8, M.2 Interface: 1 SATA/PCIe 3.0 x4	Cooling System	2x 80mm PWM Rear Chassis Fans (9.4k RPM) 3x 80mm high-performance fan(s) (9.4k RPM)
Integrated Onboard	SATA Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10	Form Factor	Form Factor 4U Rackmount
	LAN 2 RJ45 Gigabit Ethernet LAN ports	Dimensions	Dimensions Height :17.8" (452 mm), Width :7" (178 mm),Depth :7" (178 mm)
Add-on Options	Raid Card Optional	<p style="text-align: center;">Email : Info@tyronesystems.com</p> <p style="text-align: center;">For more/current product information, Visit www.tyronesystems.com</p>	
	Optical Drive Optional		
Front Panel			
LAN	2 RJ45 Gigabit Ethernet LAN ports		
USB	6 USB 2.0 port(s) (4 via header; 2 rear), 5 USB 3.2 Gen1 port(s) (2 via header; 2 rear; 1 type A)		
Video	1 VGA port		
TPM	1 TPM Header		
Serial	1 COM port(Rear)		